

TrueNorthHDD

LRG 1010

SPECIFICATIONS







DESCRIPTION	
MODEL	LRG 1010
GAWR	10,000 lbs.
Overall Length	Appox. 154 in.
Overall Width	102 in.
Reel Capacity	10 ft. x 60 in.
Empty Weight	1,800 lbs.
	RUNNING GEAR
Axle	10,000 lbs.
Brakes	Electric
Tires	ST215/75 R17.5 LRH
Wheels	17.5 X 6.75 8 Bolt White Mod
	FRAME
Main Frame	4 x 6 in. Rectangular tube
Gun Rack Shell	4 x 4 in. Square tube
Gun Rack Support	3 1/2 x 3 1/2 in. Square tube
Gun Rack	¾ in. x 5 ½ in. flat
Tongue	4 x 6 in. Rectangular tube
Light Boxes	4 x 6 in. Rectangular tube
Fenders	12 in. Jr Channel
	SPINDLE BAR
Material	2 1/2 in Diam. CRR
	ELECTRIAL
Plug	7 RV molded plug
Wiring	Enclosed in conduit w/ junction boxes
ŭ	Connections soldered & shrink wrapped
Lights	Lights – Standard LED package
SAFETY	
Chains	Rated to match
Break Away	Battery, battery box, and switch
Decals	Warning decals & reflective tape
	ACCESSORIES
Wheel Chocks	Rumber
Jack	Single 12K spring loaded drop leg
	FINISH
PPG Paint	Industrial urethane. White, Black,
	Orange, Yellow.
	HYDRAULICS
Cylinders	2 x 20 in. welded
Pump	Dual Manual
	95 cu. In.
Fluid	Dexron III / Mercon A.T.F.
Fidio	- DOMON IN THOROUGH FET.1